


PCB LAYOUT/TOP VIEW

TABLE 1

EA	GREEN 9 — 10	GREEN 11 — 12 ORANGE
9A	YELLOW 9 — 10	GREEN 11 — 12
LED CODE	LEFT LED	RIGHT LED

NOTES:

- MATERIAL/FINISH: SEE TABLE.
- ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 1.5A MAX.
 - VOLTAGE RATING: 150VAC MAX.
 - INSULATION RESISTANCE: 500MΩ MIN.
 - DIELECTRIC WITHSTANDING VOLTAGE: 1000VAC
- MECHANICAL CHARACTERISTICS:
 - DURABILITY: 750 CYCLES
 - OPERATING TEMPERATURE: -40°C TO +85°C.
 - FOR WAVE SOLDERING LEAD-FREE PROCESS.
 - MATES WITH MODULAR PLUG CONFORMING TO FCC PART 68, SUBPART F.
- THE CONNECTOR IS RoHS COMPLIANT.
- SPEC. PLS. REFER TO PS-31570-XXXXX-XXX
- PACKAGE PLS. REFER TO 31570-XXXXX-XXX-PCK
- DATE CODE: XXXXX



P/N RULE CODE:

31570-R XX 00 X 00 T -001

- R: ROHS
- LED CODE:
 - 9A: L=YELLOW, R=GREEN POLARITY ACCORD
 - EA: L=GREEN, R=G+O POLARITY ACCORD
- CIRCUIT TYPE:
 - 00: W/O TRANSFORMER
- 001: NORMAL
- PACKING:
 - T: TRAY PACKAGE
- MECHANICAL SERIES (EMI TAB)
 - 00- W/O EMI TAB
- PLATING CODE:
 - 1: GOLD FLASH 2: Au 6u"
 - 3: Au 10u" 4: Au 15u"
 - 5: Au 30u"

NO	DESCRIPTION	Q'TY	MATERIAL	FINISH
D	LED	2		SEE TABLE 1
C	SHELL	1	BRASS C2680 T=0.15mm	NICKEL PLATING
B	TERMINAL	8	PHOSPHOR BRONZE φ0.45mm	GOLD PLATING, NICKEL UNDERPLATED
A	HOUSING	1	PA6T	UL 94V-0, BLACK

QUALITY SYMBOLS MAJOR Ⓢ CRITICAL Ⓢ	DRAWN BY DENG JIANXIANG '200401 DATE	ACES ELECTRONICS	
GENERAL TOLERANCES (UNLESS SPECIFIED)	CHECKED BY TENG CHANG HO '200401 DATE	TITLE RJ45, TAB UP, R/A, STP, LED	
X. ±0.5 .X ±0.30 .XX ±0.20 .XXX ±0.10 ANGLES ±1°	APPROVED BY KUO JUNG HSUN '200401 DATE	UNITS mm	SIZE A4
	SCALE 1:1	SHEET NO. 1 OF 1	REV A
		RFQ NO. 31570-RXX00X00T-001	DWG NO.